

DSS 13 oz. Pro Blockout is a two-sided, blockout banner material with a smooth surface. The material offers a broad color gamut with low ink consumption and is ideal for application where complete opacity is required. The material is compatible with solvent, eco-solvent, UV and screen printing. Available in widths from 38" - 126".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Total Weight	DIN EN ISO 2286-2	375 g/m ²	13 oz/yd ²
Yarn dtex	DIN EN ISO 2060	250 / 250	250 x 250 denier
Support Cloth	DIN 60001	Polyester	Polyester
Type of Coating	N/A	PVC	PVC
Tensile Strength	DIN 53352 BS3424	1300 x 1030 N/5cm	148.46 x 117.63 lb/in
Tear Strength	DIN53356 BS3424	115 x 105 N	25.85 x 23.60 lb

Applications

	POP	Banner	Banner Stands	Block-out	Tradeshow Graphics	Display Systems	Indoor Banners
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Latex	Dye Direct
■	■	■	■		

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 3.20	38", 54", 63", 126"

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)