contr/\vision[®] Technical Data Sheet

Product Name: Edge Sealer Page: 1/2

Revision: 2 (CVNA)

Date: 01 February 2019

Product Reference: ES-CL50CY Replaces: A Authors: RAS

Description

ES-CL50CY is a 0.8" (20mm) wide, optically clear, gloss cast pvc edge sealing film featuring a polyester liner.

ES-CL50CY edge sealing film is intended to be used either in conjunction with laminating film or on its own. Edge sealing is not generally necessary, but does improve the

resistance to environmental damage and damage incurred when cleaning to enhance the durability of the graphics, as the edges are the most vulnerable areas of perforated window film, whether overlaminated or not. Edge sealing is especially worth consideration for vehicle graphics.

Typical Properties	
PROPERTY	VALUE
Face film	Clear gloss cast PVC
Film thickness	2 mil (50μm)
Hole pattern	N/A
Adhesive	Transparent, permanent, solvent polyacrylate
Liner	Single-sided silicone-coated polyester 3 mil
Liner weight	
Application temperature	Minimum: 50°F (10°C) air and substrate
Peel adhesion 24 hours	
Peel adhesion 1 month	
Removability	
Durability	3 years Vertical applications only. This refers to the overlaminate itself, and not any extra durability that it gives the printed image.
Shrinkage	
Service temp	
Shelf life	2 years Under ordinary condition at temperature of 72°F (22°C) and relative humidity of 50-55%
Other info	

contr/\vision® Technical Data Sheet

Product Name: Edge Sealer Page: 2/2

ES-CL50CY

Revision: 2 (CVNA)

Date: 01 February 2019

Replaces: A
Authors: RAS

Regulations

Product Reference:

Substrate Recommendations

This product is not recommended for use on glass with coatings such as anti-reflective, self-cleaning and scratch-resistance, which may be damaged during film removal.

Application Recommendations

After installing Contra Vision® Perforated Window Film, apply strips of ES-CL50CY to the edges of the graphic so each strip is equally placed over the perforated material and substrate.

Printing Recommendations

N/A

Contact Information

Supplier: Contra Vision North America, Inc. Tel. +1 770 993 6262

3330 Cumberland Blvd, Suite 500 Email: usasales@contravision.com

Atlant Web: www.contravision.com

USA

This document is intended as a source of information, is given without guarantee, and does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific intended purpose.

All trademarks in this datasheet are ©Contra Vision Ltd