Wide Format / Sol-Eco-UV-Latex Media

READ SCO.

20 mil Standard Energy Magnetic Roll

Is a 20 mil printable magnet

MAG020

- Adheres to steel and magnetic surfaces
- Interchangeable vehicle signage, warehouse labeling and POP displays
- With standard or HiPro adhesive, standard and high energy
- Excellent white point and dyne value on print surfaces
- Direct printable matte/gloss white vinyl is compatible with solvent, eco-solvent and UV inks

Lamination & Mounting

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

Solvent, Eco-solvent, Uv Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, uv curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

Roll Configurations

FINISHED ROLLS	CORE	PRINT SIDE
24"X50'	3″	PSO
40"X50'	3″	PSO
48"X50'	3″	PSO

* CALL FOR ADDITIONAL SIZES

ORDER TODAY: readinkjet.com

Physical Specifications

CALIPER (mil): 20 mil FINISH: Matte MAGNETIC PROPERTIES: BR (GS): ≥1550 / HCB (Oe): ≥1100 / HCJ (Oe): ≥2000 / BH (MAX) (MGOe): 0.5 - 0.65 OPTIMUM ENVIRONMENT: 30-70% RH