

ProFlex 13 oz. Blockout is a two-sided, blockout banner material with a smooth surface. The material offers a broad color gamut with low ink consumption and is ideal for application where complete opacity is required. The material is compatible with solvent, eco-solvent, UV and screen printing. Available in widths from 38" - 126".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Total Weight	DIN EN ISO 2286-2	440 g/m ²	13 oz/yd ²
Support Cloth	DIN 60001	Polyester	Polyester
Type of Coating	N/A	PVC	PVC
Tensile Strength	ISO 13934-1 : 2013 C.R.E. Strip Method	1127 x 717 N/5cm	128.7 x 81.88 lb/in
Tear Strength	ISO 13937-2 : 200 C.R.E Single Tear Method	56 x 54 N	12.59 x 12 lb
Elongation	ISO 13934-1: 2013 C.R.E. Strip Method	29 x 31%	

Applications

	POP	Banner	Banner Stands	Block-out	Tradeshow Graphics	Display Systems	Indoor Banners
Applications	■	■	■	■	■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Latex	Dye Direct
■	■	■	■		

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 3.20	38", 54", 63", 126"

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)