

# PSHGP

## 2 mil High Gloss Polyester UV Laminate Film



### A High Gloss Polyester Lamination Film

- Ideal for photographic prints that require a high gloss finish
- Polyester base gives this product the highest gloss possible, surpassing PVC films
- Optically clear adhesive for superior clarity
- Recommended for abrasion resistance
- Extends the life of your print and provides UV resistance

### Finishing Recommendations

**Surfaces:** Read&Co. laminates are specifically design to work with Read&Co. inkjet media. Read&Co. recommends that you use Read&Co. inkjet media to get the best results. All testing has been done with our branded media.

**Surface Protection:** Ensure that your graphic is completely dry prior to laminating. If inks are not dry before lamination the adhesion of the laminate can be adversely affected; outgassing of inks may occur, causing silvering to form under the laminate.

**Laminating:** If too much tension is applied during lamination, the product may curl toward the laminated side, and the edges may lift from the release liner and/or the application surface. Always double-check your machine settings.

### Care And Maintenance

**Packaging:** If the output is being sent without mounting to a substrate such as FoamCore, always roll laminated prints with the graphic facing outward. It is not recommended to ship in a tube smaller than 6" in diameter.

**Field Care & Maintenance:** If graphics should become dirty while out in the field; we suggest using a damp cloth to remove dust and dirt. Do Not use Windex® or other cleaner; these products contain silicon and will damage the graphic. If a damp cloth doesn't do the job, use a solution up to 20% isopropyl alcohol (one part isopropyl alcohol to four parts water), and gently wipe clean. Markings can be removed by gently using a rubber eraser.

**Material Handling:** Unused laminate material should be placed back in its original packaging and stored at 70°F (21°C) for no more than 1 year; to obtain maximum adhesion.

### Roll Configurations

FINISHED ROLLS	CORE	LINER SIDE
38"X150'	3"	In
51"X150'	3"	In
54"X150'	3"	In

\* CALL FOR ADDITIONAL SIZES

**ORDER TODAY:**  
[readinkjet.com](http://readinkjet.com)

### Physical Specifications

CALIPER (mil): 3  
 POLYESTER (mil): 2  
 ADHESIVE (mil): 1  
 MINIMUM APPLICATION TEMP: 50° F (10° C)  
 UV PROTECTION: Yes  
 LINER TYPE: Craft, PE Coated

**FOR MORE INFORMATION:** 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | [readinkjet.com](http://readinkjet.com)