

PSMFL4

4 mil Floor Graphic Textured Laminate Film

READ&Co.

A Textured Floor Lamination Film

- Durable and recommended for abrasion resistance
- Excellent rigidity and lay flat features
- UL Rated for indoor floor applications
- Ideal trade show graphics and areas with high lighting or glare
- Countertop and table applications

Finishing Recommendations

Surfaces: Read&Co. laminates are specifically design to work with Read&Co. inkjet media. Read&Co. recommends that you use Read&Co. inkjet media to get the best results. All testing has been done with our branded media.

Surface Protection: Ensure that your graphic is completely dry prior to laminating. If inks are not dry before lamination the adhesion of the laminate can be adversely affected; outgassing of inks may occur, causing silvering to form under the laminate.

Laminating: If too much tension is applied during lamination, the product may curl toward the laminated side, and the edges may lift from the release liner and/or the application surface. Always double-check your machine settings.

Care And Maintenance

Packaging: When shipping trade show panels, always roll laminated prints with the heavier gauge material facing out. It is not recommended to ship in a tube smaller than 10" in diameter (12" in diameter is ideal).

Field Care & Maintenance: If graphics should become dirty while out in the field; we suggest using a damp cloth to remove dust and dirt. Do Not use Windex® or other cleaner; these products contain silicon and will damage the graphic. If a damp cloth doesn't do the job, use a solution up to 20% isopropyl alcohol (one part isopropyl alcohol to four parts water), and gently wipe clean. Markings can be removed by gently using a rubber eraser.

Material Handling: Unused laminate material should be placed back in its original packaging and stored at 70°F (21°C) for no more than 1 year; to obtain maximum adhesion.

Roll Configurations

FINISHED ROLLS	CORE	LINER SIDE
54"X150'	3"	In

* CALL FOR ADDITIONAL SIZES

ORDER TODAY:
readinkjet.com

Physical Specifications

CALIPER (mil): 5
 POLYPROPLYLENE (mil): 3.75
 ADHESIVE (mil): 1
 FINISH: Velvet Textured Matte
 ADHESIVE TYPE: Permanent Acrylic
 MINIMUM APPLICATION TEMP: 50° F (10° C)
 LINER TYPE: Craft Paper

FOR MORE INFORMATION: 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | readinkjet.com