

# SEMRLD

## 16 oz. Emerald Backlit Banner FR



### A Premium 16 oz. MATTE Backlit Banner Vinyl

- Super smooth surface
- Compatible with solvent, eco solvent, UV curable and latex inks
- Great density and an evenly diffused, consistent finish
- Ideal for the most demanding backlit applications
- Great for oversized backlit displays
- Delicate fabric structure and super clean image
- NFPA 701 fire retardant certificate
- ASTM D635-2014 fire certificate

### Lamination & Mounting

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

### Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

### Roll Configurations

FINISHED ROLLS	CORE	PRINT SIDE
126"x150'	3"	PSO
197"x150'	3"	PSO

\* CALL FOR ADDITIONAL SIZES

**ORDER TODAY:**  
[readinkjet.com](http://readinkjet.com)

### Physical Specifications

BASIS WEIGHT (grams/m<sup>2</sup>): 560 (16.5 oz.)  
 TENSIL STRENGTH: 500D X 500D; 28 X 28  
 MATERIAL: Polyester PVC  
 GLOSS LEVEL: Matte  
 OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) /  
 30-70% RH

**FOR MORE INFORMATION:** 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | [readinkjet.com](http://readinkjet.com)