

SPEARL

15 oz. Pearl Super Smooth Two Sided
Premium Banner FR

READ&Co.

A 15 oz. Premium Two Sided Matte Coated Fire Resistant Banner

- Premium coated banner resists cracking in extreme weather environments
- Good color brilliance and image definition
- Two sided printable with consistent coating finish from front to back
- Smooth texture for up close viewing and high resolution printing
- Excellent for indoor banner applications
- Banner can be sewn and or grommeted
- NFPA 701 fire retardant certificate

Lamination & Mounting

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

Roll Configurations

FINISHED ROLLS	CORE	PRINT SIDE
38"x164'	3"	PSI
54"x164'	3"	PSI
63"x164'	3"	PSI
104"x164'	3"	PSI
126"x164'	3"	PSI

* CALL FOR ADDITIONAL SIZES

ORDER TODAY: readinkjet.com

Physical Specifications

BASIS WEIGHT (grams/m²): 510 (15 oz.)
 CALIPER: 16 mil
 TENSIL STRENGTH: 300D X 300D; 42 X 42
 MATERIAL: PVC
 GLOSS LEVEL: Semi Matte
 OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) /
 30-70% RH

FOR MORE INFORMATION: 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | readinkjet.com