

Technical Data Sheet VorTex™ Woven D345

VorTex[™] Woven D345 is a 10.2 oz., heavy, woven 100% polyester material. The material has a canvas structure with a bright white point allowing for a wide color gamut. The woven product is REACH compliant. VorTex Woven D345 is printable via direct dye-sublimation, UV, Latex and transfer. Available in widths of 122" and 198".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH	
Base Fabric		100% Polyester		
Total Weight	ASTM D645	345 g/m²	10.2 oz/yd²	
Fire Resistance	DIN EN 13501-1			

Applications

	Banner Stands	Banners Indoor	POP Display	Light Box	Display Systems	Theater	Art Reproductions	Wall Advertising
Application								

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

Available Sizes

Metric (m)	English (inches)
3.10, 5.05	122, 198

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

ULTRAFLEX

www.ultrafleXX.com

Ultraflex Systems Inc. Headquarters 6333 Pelican Creek Circle, Riverview, FL 33578 P: (973)627-8608 Email: sales@Ultraflexx.com Ultraflex Systems Inc. 1578 Sussex Turnpike, Bldg. 4 Randolph, NJ 07869 P: (973)627-8608 F: (973)627-8506 Email: sales@ultraflexx.com Ultraflex Europe Unit 15 Eltisley Business Park Abbotsley, Cambridgeshire UK PE19 6TX Phone: (44)1767-677-100

Email: sales@ultraflexeurope.com